

API RP 7G									
SPECIFICATIONS FOR USED DRILL PIPE									
DWB					YELLOWBAND				
Nom. OD (in)	Nom. Wt. (lb/ft)	ID (in)	Minimum Wall (80°/a)	TJ OD (in) Min	Minimum Max	Wall (70°/a)	TJ OD (in) Min	Max	
2.375	4.85	1.995	0.152	2.304	2.446	0.133	2.28	2.47	
2.375	6.65	1.815	0.224			0.196			
2.875	6.85	2.441	0.174	2.789	2.961	0.152	2.76	2.99	
2.875	10.4	2.151	0.29			0.253			
3.5	9.5	2.992	0.203	3.395	3.605	0.178	3.36	3.64	
3.5	13.3	2.764	0.294			0.258			
3.5	15.5	2.602	0.359			0.314			
4	11.85	3.476	0.21	3.88	4.12	0.183	3.84	4.16	
4	14	3.34	0.264			0.231			
4	15.7	3.24	0.304			0.266			
4.5	13.75	3.958	0.217	4.365	4.635	0.19	4.32	4.68	
4.5	16.6	3.826	0.27			0.236			
4.5	20	3.64	0.344			0.301			
4.5	22.82	3.5	0.4			0.35			
5	16.25	4.408	0.237	4.85	5.15	0.207	4.8	5.2	
5	19.5	4.276	0.29			0.253			
5	25.6	4	0.4			0.35			
5.5	19.2	4.892	0.243	5.335	5.665	0.213	5.28	5.72	
5.5	21.9	4.778	0.289			0.253			
5.5	24.7	4.67	0.332			0.29			
6.625	25.2	5.965	0.264	6.426	6.824	0.231	6.36	6.89	
6.625	27.7	5.901	0.29			0.253			154



